



ElastiTag®

Digital Print Capabilities

TYPE:

Minimum POSITIVE type is 3 pt.(sans serif); 4 pt.(serif)
Minimum REVERSE type is 4 pt.(sans serif); 5 pt.(serif)
Microprint is available for security/anti-counterfeit applications:
POSITIVE Sans Serif only - .8 pt (Magnification required for readability)

IMAGE AREA:

Maintain .125" margin from dieline for copy and graphics.
Colors may bleed if a solid color is on all sides of tag.

COLOR SPECIFICATIONS:

Digital printing is done in 4 color process.
Pantone spot colors are available on special order.
Indichrome 7-color process printing is also available.
Metallic and fluorescent inks can not be printed on the digital press.

**SCREENS/TINTS/
GRADIENTS:**

Screens may range from 100% to a minimum of 1%.

LINES/RULES:

Minimum POSITIVE line rule is .22 pt/.003". Minimum REVERSE line rule is .45 pt/.006"

COLOR PROOFS:

PDF files are emailed for initial layout approval.
Color press proofs are available on request at an additional charge.
(These are printed with the digital press on the actual tag material.)

DIELINES:

Contact one of our Customer Service representatives for a listing of the available die shapes. NOTE: Custom dies can also be created for you. Prices vary.

Variable Data Printing is also available; Call for more information.

BEDFORD INDUSTRIES, Inc.

1659 Rowe Avenue Worthington, MN 56187

Ph: 1-877-BEDFORD (233-3673) in USA & Canada or 1-507-376-4136

www.bedfordind.com www.elastitag.com